



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

Address: COMMISSIONER FOR PATENTS

P.O. Box 1450

Alexandria, Virginia 22313-1450

www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/585,865	07/11/2006	Koichi Miyachi	LB-1035-644	7753
23117 7590 09/13/2011 NIXON & VANDERHYE, PC 901 NORTH GLEBE ROAD, 11TH FLOOR ARLINGTON, VA 22203				
EXAMINER				
HICKS, CHARLES V				
ART UNIT		PAPER NUMBER		
2629				
MAIL DATE		DELIVERY MODE		
09/13/2011		PAPER		

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

# Office Action Summary

**Application No.**

10/585,865

**Applicant(s)**

MIYACHI ET AL.

**Examiner**

CHARLES V. HICKS

**Art Unit**

2629

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --  
**Period for Reply**

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

**Status**

- 1) ☒ Responsive to communication(s) filed on 17 March 2011.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ An election was made by the applicant in response to a restriction requirement set forth during the interview on \_\_\_\_; the restriction requirement and election have been incorporated into this action.
- 4) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

**Disposition of Claims**

- 5) ☒ Claim(s) 1-23 is/are pending in the application.
- 5a) Of the above claim(s) \_\_\_\_ is/are withdrawn from consideration.
- 6) ☐ Claim(s) \_\_\_\_ is/are allowed.
- 7) ☒ Claim(s) 1-23 is/are rejected.
- 8) ☐ Claim(s) \_\_\_\_ is/are objected to.
- 9) ☐ Claim(s) \_\_\_\_ are subject to restriction and/or election requirement.

**Application Papers**

- 10) ☐ The specification is objected to by the Examiner.
- 11) ☒ The drawing(s) filed on 07/11/2006 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 12) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

**Priority under 35 U.S.C. § 119**

- 13) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All b) ☐ Some \* c) ☐ None of:
- 1) ☒ Certified copies of the priority documents have been received.
  - 2) ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_.
  - 3) ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

**Attachment(s)**

- 1) ☒ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- 3) ☒ Information Disclosure Statement(s) (PTO-804)
- 4) ☐ Interview Summary (PTO-413)
- 5) ☐ Notice of Informal Patent Application
- 6) ☐ Other: \_\_\_\_
- Paper No(s)/Mail Date 06/27/2011, 08/12/2011, 08/30/2011

### **DETAILED ACTION**

A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 03/17/2011 has been entered.

Claims 1, 4-5 and 15 have been amended. Claims 1-23 are pending.

### ***Claim Rejections - 35 USC § 103***

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

This application currently names joint inventors. In considering patentability of the claims under 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to consider the applicability of 35 U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g) prior art under 35 U.S.C. 103(a).

Claims 1, 3-4, 6, 9, 15, 17-18 and 22 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yamaguchi et al. (US 6,266,109) in view of Someya et al. (US 7,034,788).

In reference to claim 1, Yamaguchi teaches a display apparatus, comprising display elements including a medium injected and sealed between a pair of substrates at least one of which is transparent (Yamaguchi, col. 11, ll. 39-46),

the medium changing in magnitude of optical anisotropy upon application of voltage (Yamaguchi, Abstract; col. 1, ll. 45-50),

each of the display elements containing colors required to produce a color image display, so as to produce a color image display (Yamaguchi, col. 1, ll. 9-12).

different voltages being applied to the display elements so as to display the colors required to produce a color image display, applied to electrodes across said pair of substrates (Yamaguchi, Abstract; col. 1, ll. 9-12).

Yamaguchi however fails to teach different voltages being applied to the display elements so as to display the colors required to produce a color image display with an identical gradation, wherein voltages differing in voltage values are applied, so that a first color corresponding to a first voltage has a first gradation and a second color different from said first color corresponding to a second voltage different from said first voltage has said first gradation to correct a wavelength dispersion of said optical anisotropy of the medium.

Someya discloses an image data processing device, analogous in art with that of Yamaguchi, comprising different voltages being applied to the display elements so as to display the colors required to produce a color image display with an identical gradation (Someya, col. 3, ll. 42-col. 4, ll. 3, voltage for correcting an image data representing a gray-scale level of an image to be displayed; col. 6, ll. 44-67, higher voltage and corrected voltages; col. 10, ll. 34-64, application voltage to correct an image transmittance; col. 45, ll.19-28, red, green and blue color),

wherein voltages differing in voltage values are applied, so that a first color corresponding to a first voltage has a first gradation and a second color different from said first color corresponding to a second voltage different from said first voltage has said first gradation, wherein the first voltage and the second voltage are selected according to transmittance of said optical anisotropy of the medium that corrects wavelength dispersion (Someya, col. 18, ll. 35-39, correction voltages; col. 3, ll. 42-col. 4, ll. 3, voltage for correcting an image data representing a gray-scale level of an image to be displayed; col. 15, ll. 28-col. 16, ll. 8, applied voltage to correct transmittance, therefore, wavelength dispersion).

At the time the invention was made it would have been obvious to one having ordinary skill in the art to modify the image display device of Yamaguchi to comprise different voltages being applied to the display elements so as to display the colors required to produce a color image display with an identical gradation, wherein voltages differing in voltage values are applied, so that a first color corresponding to a first voltage has a first gradation and a second color different from said first color

corresponding to a second voltage different from said first voltage has said first gradation to correct a wavelength dispersion of said optical anisotropy of the medium, as taught by Someya.

As one of ordinary skill in the art would appreciate, the suggestion/motivation for doing so would have been to optimize a change in transmittance of a liquid crystal display (Someya, col. 1, ll. 8-20).

Claim 3 is rejected as being dependent on rejected claim 1 as discussed above and further, Yamaguchi as modified by Someya teaches wherein the colors required to produce a color image display are three colors of RGB (Yamaguchi, col. 13, ll. 37-40).

In reference to claim 4, Yamaguchi teaches a display apparatus, comprising: display elements including a medium injected and sealed between a pair of substrates at least one of which is transparent (Yamaguchi, col. 11, ll. 39-46),

the medium changing in magnitude of optical anisotropy upon application of voltage (Yamaguchi, Abstract; col. 1, ll. 45-50),

each of the display elements containing colors to produce a color image display, so as to produce a color image display (Yamaguchi, col. 1, ll. 9-12),

and wherein the medium exhibits optical isotropy in absence of an electric field and exhibits optical anisotropy under applied voltage (Yamaguchi, col. 3, ll. 21-35).

Yamaguchi however fails to teach different voltages being applied to the display elements so as to display the colors required to produce a color image display with an

identical gradation, wherein voltages differing in voltage values are applied, so that a first color corresponding to a first voltage has a first gradation and a second color different from said first color corresponding to a second voltage different from said first voltage has said first gradation, wherein the first voltage and the second voltage are selected according to a transmittance of said optical anisotropy of the medium that corrects wavelength dispersion.

Someya discloses an image data processing device, analogous in art with that of Yamaguchi, comprising different voltages being applied to the display elements so as to display the colors required to produce a color image display with an identical gradation (Someya, col. 3, ll. 42-col. 4, ll. 3, voltage for correcting an image data representing a gray-scale level of an image to be displayed; col. 6, ll. 44-67, higher voltage and corrected voltages; col. 10, ll. 34-64, application voltage to correct an image transmittance; col. 45, ll. 19-28, red, green and blue color),

wherein voltages differing in voltage values are applied, so that a first color corresponding to a first voltage has a first gradation and a second color different from said first color corresponding to a second voltage different from said first voltage has said first gradation, wherein the first voltage and the second voltage are selected according to transmittance of said optical anisotropy of the medium that corrects wavelength dispersion (Someya, col. 18, ll. 35-39, correction voltages; col. 3, ll. 42-col. 4, ll. 3, voltage for correcting an image data representing a gray-scale level of an image to be displayed; col. 15, ll. 28-col. 16, ll. 8, applied voltage to correct transmittance, therefore, wavelength dispersion).

At the time the invention was made it would have been obvious to one having ordinary skill in the art to modify the image display device of Yamaguchi to comprise different voltages being applied to the display elements so as to display the colors required to produce a color image display with an identical gradation, wherein voltages differing in voltage values are applied, so that a first color corresponding to a first voltage has a first gradation and a second color different from said first color corresponding to a second voltage different from said first voltage has said first gradation to correct a wavelength dispersion of said optical anisotropy of the medium, as taught by Someya.

As one of ordinary skill in the art would appreciate, the suggestion/motivation for doing so would have been to optimize a change in transmittance of a liquid crystal display (Someya, col. 1, ll. 8-20).

Claim 6 is rejected as being dependent on rejected claim 1 as discussed above and further, Yamaguchi as modified by Someya teaches wherein the medium is comprised by molecules having an ordered structure less than optical wavelengths either under applied voltage or in absence of applied voltage (Yamaguchi, col. 9, ll. 51-58).

Claim 9 is rejected as being dependent on rejected claim 1 as discussed above and further, Yamaguchi as modified by Someya teaches wherein the medium is



comprised by a liquid crystal microemulsion (Yamaguchi, col. 5, ll. 24-40; col. 6, ll. 45-64).

In reference to claim 15, Yamaguchi teaches a display element in a display apparatus, comprising a plurality of display elements (Yamaguchi, col. 11, ll. 39-46), each display element containing colors required to produce a color image display, so as to produce a color image display (Yamaguchi, col. 1, ll. 9-12),

a medium being injected and sealed between a pair of substrates at least one of which is transparent (Yamaguchi, col. 11, ll. 39-46),

the medium changing in magnitude of optical anisotropy upon application of voltage (Yamaguchi, Abstract; col. 1, ll. 45-50).

Yamaguchi however fails to teach different voltages being applied to the display elements so as to display the colors required to produce a color image display with an identical gradation, wherein voltages differing in voltage values are applied, so that a first color corresponding to a first voltage has a first gradation and a second color different from said first color corresponding to a second voltage different from said first voltage has said first gradation to correct a wavelength dispersion of said optical anisotropy of the medium.

Someya discloses an image data processing device, analogous in art with that of Yamaguchi, comprising different voltages being applied to the display elements so as to display the colors required to produce a color image display with an identical gradation (Someya, col. 3, ll. 42-col. 4, ll. 3, voltage for correcting an image data representing a

gray-scale level of an image to be displayed; col. 6, ll. 44-67, higher voltage and corrected voltages; col. 10, ll. 34-64, application voltage to correct an image transmittance; col. 45, ll. 19-28, red, green and blue color),

wherein voltages differing in voltage values are applied, so that a first color corresponding to a first voltage has a first gradation and a second color different from said first color corresponding to a second voltage different from said first voltage has said first gradation, wherein the first voltage and the second voltage are selected according to transmittance of said optical anisotropy of the medium that corrects wavelength dispersion (Someya, col. 18, ll. 35-39, correction voltages; col. 3, ll. 42-col. 4, ll. 3, voltage for correcting an image data representing a gray-scale level of an image to be displayed; col. 15, ll. 28-col. 16, ll. 8, applied voltage to correct transmittance, therefore, wavelength dispersion).

At the time the invention was made it would have been obvious to one having ordinary skill in the art to modify the image display device of Yamaguchi to comprise different voltages being applied to the display elements so as to display the colors required to produce a color image display with an identical gradation, wherein voltages differing in voltage values are applied, so that a first color corresponding to a first voltage has a first gradation and a second color different from said first color corresponding to a second voltage different from said first voltage has said first gradation to correct a wavelength dispersion of said optical anisotropy of the medium, as taught by Someya.

As one of ordinary skill in the art would appreciate, the suggestion/motivation for doing so would have been to optimize a change in transmittance of a liquid crystal display (Someya, col. 1, ll. 8-20).

Claim 17 is rejected as being dependent on rejected claim 4 as discussed above and further, Yamaguchi as modified by Someya teaches wherein the colors required to produce a color image display are the three colors of RGB (Yamaguchi, col. 13, ll. 37-40).

Claim 18 is rejected as being dependent on rejected claim 4 as discussed above and further, Yamaguchi as modified by Someya teaches wherein the medium is comprised by molecules having an ordered structure less than the optical wavelengths either under applied voltage or in absence of applied voltage (Yamaguchi '109, col. 9, ll. 51-58).

Claim 22 is rejected as being dependent on rejected claim 15 as discussed above and further Yamaguchi as modified by Someya teaches wherein the medium exhibits optical isotropy in absence of an electrical field and exhibits optical anisotropy under applied voltage (Yamaguchi, col. 3, ll. 21-35).

Claims 2, 8, and 16 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yamaguchi et al. (US 6,266,109) as modified by Someya et al. (US 7,034,788) and further in view of Takeuchi et al. (US 2001/0024178).

Claim 2 is rejected as being dependent on rejected claim 1 as discussed above and further, Yamaguchi as modified by Someya however fails to teach wherein the voltages applied are determined based on a lookup table which associates gradations of an image displayed by the display apparatus with the voltages applied to the display elements.

Takeuchi discloses a display system, analogous in art with that of Yamaguchi as modified by Someya, wherein the voltages applied are determined based on a lookup table which associates gradations of an image displayed by the display apparatus with the voltages applied to the display elements (Takeuchi, pg. 22, par. 378-379).

At the time the invention was made, it would have been obvious to one having ordinary skill in the art to modify the display device of Yamaguchi as modified by Someya wherein the voltages applied are determined based on a lookup table which associates gradations of an image displayed by the display apparatus with the voltages applied to the display elements, as taught by Takeuchi.

As one of ordinary skill in the art would appreciate, the suggestion/motivation for doing so would have been a display with memory and table creation for storing luminance correction data for correcting a luminance dispersion of the display (Takeuchi, pg. 3, par. 37).

Claim 8 is rejected as being dependent on rejected claim 1 as discussed above and further, Yamaguchi as modified by Someya however fails to teach wherein the medium is comprised by molecules showing a cubic phase or a smectic D phase.

Takeuchi discloses a display system, analogous in art with that of Yamaguchi as modified by Someya, wherein the medium is comprised by molecules showing a cubic phase or a smectic D phase (Takeuchi, pg. 8, par. 170).

At the time the invention was made, it would have been obvious to one having ordinary skill in the art to modify the display device of Yamaguchi as modified by Someya wherein the medium is comprised by molecules showing a cubic phase or a smectic D phase, as taught by Takeuchi.

As one of ordinary skill in the art would appreciate, the suggestion/motivation for doing so would have been the addition of strength, toughness, and durability (Takeuchi, pg. 8, par. 170).

Claim 16 is rejected as being dependent on rejected claim 4 as discussed above and further, Yamaguchi as modified by Someya however fails to teach wherein the voltages applied are determined based on a lookup table which associates gradations of an image displayed by the display apparatus with the voltages applied to the display elements.

Takeuchi discloses a display system, analogous in art with that of Yamaguchi as modified by Someya, wherein the voltages applied are determined based on a lookup

table which associates gradations of an image displayed by the display apparatus with the voltages applied to the display elements (Takeuchi, pg. 22, par. 378-379).

At the time the invention was made, it would have been obvious to one having ordinary skill in the art to modify the display device of Yamaguchi as modified by Someya wherein the voltages applied are determined based on a lookup table which associates gradations of an image displayed by the display apparatus with the voltages applied to the display elements, as taught by Takeuchi.

As one of ordinary skill in the art would appreciate, the suggestion/motivation for doing so would have been a display with memory and table creation for storing luminance correction data for correcting a luminance dispersion of the display (Takeuchi, pg. 3, par. 37).

Claims 5, 20, 21 and 23 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yamaguchi et al. (US 6,266,109) as modified by Someya et al. (US 7,034,788) and further in view of Yoo et al. (US 6,636,289).

In reference to claim 5, Yamaguchi teaches a display apparatus, comprising: display elements including a medium injected and sealed between a pair of substrates at least one of which is transparent (Yamaguchi, col. 11, ll. 39-46),

the medium changing in magnitude of optical anisotropy upon application of voltage (Yamaguchi, Abstract; col. 1, ll. 45-50),

each of the display elements containing colors to produce a color image display, so as to produce a color image display (Yamaguchi, col. 1, ll. 9-12),

Yamaguchi however fails to teach different voltages being applied to the display elements so as to display the colors required to produce a color image display with an identical gradation, wherein voltages differing in voltage values are applied, so that a first color corresponding to a first voltage has a first gradation and a second color different from said first color corresponding to a second voltage different from said first voltage has said first gradation to correct a wavelength dispersion of said optical anisotropy of the medium.

Someya discloses an image data processing device, analogous in art with that of Yamaguchi, comprising different voltages being applied to the display elements so as to display the colors required to produce a color image display with an identical gradation (Someya, col. 3, ll. 42-col. 4, ll. 3, voltage for correcting an image data representing a gray-scale level of an image to be displayed; col. 6, ll. 44-67, higher voltage and corrected voltages; col. 10, ll. 34-64, application voltage to correct an image transmittance; col. 45, ll.19-28, red, green and blue color),

wherein voltages differing in voltage values are applied, so that a first color corresponding to a first voltage has a first gradation and a second color different from said first color corresponding to a second voltage different from said first voltage has said first gradation, wherein the first voltage and the second voltage are selected according to transmittance of said optical anisotropy of the medium that corrects wavelength dispersion (Someya, col. 18, ll. 35-39, correction voltages; col. 3, ll. 42-col.

4, ll. 3, voltage for correcting an image data representing a gray-scale level of an image to be displayed; col. 15, ll. 28-col. 16, ll. 8, applied voltage to correct transmittance, therefore, wavelength dispersion).

At the time the invention was made it would have been obvious to one having ordinary skill in the art to modify the image display device of Yamaguchi to comprise different voltages being applied to the display elements so as to display the colors required to produce a color image display with an identical gradation, wherein voltages differing in voltage values are applied, so that a first color corresponding to a first voltage has a first gradation and a second color different from said first color corresponding to a second voltage different from said first voltage has said first gradation to correct a wavelength dispersion of said optical anisotropy of the medium, as taught by Someya.

As one of ordinary skill in the art would appreciate, the suggestion/motivation for doing so would have been to optimize a change in transmittance of a liquid crystal display (Someya, col. 1, ll. 8-20).

Yamaguchi as modified by Someya however fails to teach wherein the medium exhibits optical anisotropy in absence of an electric field and exhibits optical isotropy under applied voltage.

Yoo discloses a liquid crystal display medium, analogous in art with that of Yamaguchi as modified by Someya, wherein the medium exhibits optical anisotropy in absence of an electric field and exhibits optical isotropy under applied voltage (Yoo, col. 1, ll. 19-30; Fig. 24A, col. 16, ll. 20-34).



At the time the invention was made it would have been obvious to one having ordinary skill in the art to modify the liquid crystal medium of Yamaguchi as modified by Someya wherein the medium exhibits optical anisotropy in absence of an electric field and exhibits optical isotropy under applied voltage, as taught by Yoo.

As one of ordinary skill in the art would appreciate, the suggestion/motivation for doing so would have been to achieve a fast response time (Yoo, col. 6, ll. 1-7).

Claim 20 is rejected as being dependent on rejected claim 5 as discussed above and further, Yamaguchi as modified by Someya and Yoo teaches wherein the colors required to produce a color image display are three colors of RGB (Yamaguchi, col. 13, ll. 37-40).

Claim 21 is rejected as being dependent on rejected claim 5 as discussed above and further, Yamaguchi as modified by Someya and Yoo teaches wherein the medium is comprised by molecules having an ordered structure less than optical wavelengths either under applied voltage or in the absence of applied voltage (Yamaguchi, col. 9, ll. 51-58).

Claim 23 is rejected as being dependent on rejected claim 15 as discussed above and further, Yamaguchi as modified by Someya however fails to teach wherein the medium exhibits optical anisotropy in absence of an electric field and exhibits optical isotropy under applied voltage.

Yoo discloses a liquid crystal display medium, analogous in art with that of Yamaguchi as modified by Someya, wherein the medium exhibits optical anisotropy in absence of an electric field and exhibits optical isotropy under applied voltage (Yoo, col. 1, ll. 19-30; Fig. 24A, col. 16, ll. 20-34).

At the time the invention was made it would have been obvious to one having ordinary skill in the art to modify the liquid crystal medium of Yamaguchi as modified by Someya, wherein the medium exhibits optical anisotropy in absence of an electric field and exhibits optical isotropy under applied voltage, as taught by Yoo.

As one of ordinary skill in the art would appreciate, the suggestion/motivation for doing so would have been to achieve a fast response time (Yoo, col. 6, ll. 1-7).

Claims 7 and 11 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yamaguchi et al. (US 6,266,109) as modified by Someya et al. (US 7,034,788) and further in view of Haertling (US 4,636,786).

Claim 7 is rejected as being dependent on rejected claim 1 as discussed above and further, Yamaguchi as modified by Someya however fails to teach wherein the medium has an ordered structure showing cubic symmetry.

Haertling discloses a display device medium, analogous in art with that of Yamaguchi as modified by Someya, wherein the medium has an ordered structure showing cubic symmetry (Haertling, col. 2, ll. 65-col. 3, ll. 6).

At the time the invention was made, it would have been obvious to one having ordinary skill in the art to modify the display device medium of Yamaguchi as modified by Someya wherein the medium has an ordered structure showing cubic symmetry, as taught by Haertling.

As one of ordinary skill in the art would appreciate, the suggestion/motivation for doing so would have been to achieve high contrast, increased brightness, wide viewing angle, and reduced operating voltages (Haertling, col. 1, ll. 7-17).

Claim 11 is rejected as being dependent on rejected claim 1 as discussed above and further, Yamaguchi as modified by Someya however fails to disclose wherein the medium is comprised by a liquid crystal fine particle dispersion system showing any one of a micelle phase, a reverse micelle phase, a sponge phase, and a cubic phase.

Haertling discloses display device medium, analogous in art with that of Yamaguchi as modified by Someya, wherein the medium is comprised by a liquid crystal fine particle dispersion system showing any one of a micelle phase, a reverse micelle phase, a sponge phase, and a cubic phase (Haertling, col. 5, ll. 43-45; col. 2, ll. 65-68).

At the time the invention was made, it would have been obvious to one having ordinary skill in the art to modify the display device medium of Yamaguchi as modified by Someya wherein the medium is comprised by a liquid crystal fine particle dispersion system showing any one of a micelle phase, a reverse micelle phase, a sponge phase, and a cubic phase, as taught by Haertling.

As one of ordinary skill in the art would appreciate, the suggestion/motivation for doing so would have been a display with increased properties of brightness, greater contrast, and improved resolution (Haertling, col. 5, ll. 6-9).

Claim 10 is rejected under 35 U.S.C. 103(a) as being unpatentable over Yamaguchi et al. (US 6,266,109) as modified by Someya et al. (US 7,034,788) and further in view of Lavretovich et al. (US 6,570,632).

Claim 10 is rejected as being dependent on rejected claim 1 as discussed above and further, Yamaguchi as modified by Someya however fails to teach wherein the medium is comprised by a lyotropic liquid crystal showing any one of a micelle phase, a reverse micelle phase, a sponge phase, and a cubic phase.

Lavretovich discloses a liquid crystal cell, analogous in art with that of Yamaguchi as modified by Someya, wherein the medium is comprised by a lyotropic liquid crystal showing any one of a micelle phase, a reverse micelle phase, a sponge phase, and a cubic phase (Lavretovich, col. 2, ll. 1-17; micelle phase).

At the time the invention was made, it would have been obvious to one having ordinary skill in the art to modify the liquid crystal cell of Yamaguchi as modified by Someya to comprise a lyotropic liquid crystal showing any one of a micelle phase, a reverse micelle phase, a sponge phase, and a cubic phase, as taught by Lavretovich.

As one of ordinary skill in the art would appreciate, the suggestion/motivation for doing so would have been to achieve a perpendicular alignment as the preferred orientation (Lavretovich, col. 1, ll. 53-67).

Claim 12 is rejected under 35 U.S.C. 103(a) as being unpatentable over Yamaguchi et al. (US 6,266,109) as modified by Someya et al. (US 7,034,788), and further in view of Kenji (Patent Abstracts Of Japan, Publication number 09-243984).

Claim 12 is rejected as being dependent on rejected claim 1 as discussed above and further, Yamaguchi as modified by Someya however fails to teach wherein the medium is comprised by a dendrimer.

Kenji discloses a liquid crystal element, analogous in art with that of Yamaguchi as modified by Someya, wherein the medium is comprised by a dendrimer (Kenji, Abstract).

At the time the invention was made it would have been obvious to one having ordinary skill in the art to modify the liquid crystal medium of Yamaguchi as modified by Someya to comprise a dendrimer, as taught by Kenji.

As one of ordinary skill in the art would appreciate, the suggestion/motivation for doing so would have been to lower the driving voltage (Kenji, Abstract).

Claims 13 and 14 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yamaguchi et al. (US 6,266,109) as modified by Someya et al. (US 7,034,788) and further in view of Sato et al. (US 2003/0039770).

Claims 13 and 14 are rejected as being dependent on rejected claim 1 as discussed above and further, Yamaguchi as modified by Someya however fails to teach wherein the medium is comprised by molecules showing a cholesteric blue phase, and showing a smectic blue phase.

Sato discloses a liquid crystal display, analogous in art with that of Yamaguchi as modified by Someya, wherein the medium is comprised by molecules showing a cholesteric blue phase, and a smectic blue phase (Sato, pg. 5, par. 44)

At the time the invention was made, it would have been obvious to one having ordinary skill in the art to modify the liquid crystal display of Yamaguchi as modified by Someya, wherein the medium is comprised by molecules showing a cholesteric blue phase, and showing a smectic blue phase, as taught by Sato.

As one of ordinary skill in the art would appreciate, the suggestion/motivation for doing so would have been to broaden the temperature range of the display medium (Sato, pg. 5, par. 44).

Claim 19 is rejected under 35 U.S.C. 103(a) as being unpatentable over Yamaguchi et al. (US 6,266,109) as modified by Someya et al. (US 7,034,788) and Yoo et al. (US 6,636,289), and further in view of Takeuchi et al. (US 2001/0024178).

Claim 19 is rejected as being dependent on rejected claim 5 as discussed above and further, Yamaguchi as modified by Someya and Yoo however fails to teach wherein the voltages applied are determined based on a lookup table which associates gradations of an image displayed by the display apparatus with the voltages applied to the display elements.

Takeuchi discloses a display system, analogous in art with that of Yamaguchi as modified by Someya and Yoo, wherein the voltages applied are determined based on a lookup table which associates gradations of an image displayed by the display apparatus with the voltages applied to the display elements (Takeuchi, pg. 22, par. 378-379).

At the time the invention was made, it would have been obvious to one having ordinary skill in the art to modify the display device of Yamaguchi as modified by Someya and Yoo wherein the voltages applied are determined based on a lookup table which associates gradations of an image displayed by the display apparatus with the voltages applied to the display elements, as taught by Takeuchi.

As one of ordinary skill in the art would appreciate, the suggestion/motivation for doing so would have been a display with memory and table creation for storing luminance correction data for correcting a luminance dispersion of the display (Takeuchi, pg. 3, par. 37).

***Response to Arguments***

Applicant's arguments with respect to claims 1-23 have been considered but are moot in view of the new ground(s) of rejection.

***Conclusion***

Any inquiry concerning this communication or earlier communications from the examiner should be directed to CHARLES V. HICKS whose telephone number is (571)270-7535. The examiner can normally be reached on Monday-Thursday from 7:30 to 4:00.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Alexander Beck, can be reached on 571-272-7765. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://portal.uspto.gov/external/portal>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

/Alexander S. Beck/  
Supervisory Patent Examiner, Art Unit 2629